(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



1 (BEIG SINDIN IN SIND 1801) BEIN BEIN BEIN BEIN BIN IN AN ESHE WEN SENEL BIN BEIN BEIN BEIN BEIN BEIN BEIN BE

(43) International Publication Date 3 February 2005 (03.02.2005)

PCT

(10) International Publication Number WO 2005/010550 A1

(51) International Patent Classification⁷: G01S 3/04, 3/14

(21) International Application Number:

PCT/GB2004/002902

(22) International Filing Date: 5 July 2004 (05.07.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0316402.7

12 July 2003 (12.07.2003) GB

(71) Applicant (for all designated States except US): QINE-TIQ LIMITED [GB/GB]; Registered Office, 85 Buckingham Gate, London SW1E 6PD (GB).

(72) Inventor; and


(75) Inventor/Applicant (for US only): MACLEOD, Malcolm, David [GB/GB]; QinetiQ Malvern, Malvern

Technology Centre, St Andrews Road, Malvern, Worcs. WR14 3PS (GB).

- (74) Agent: A W S WILLIAMS; QinetiQ Ltd, IP Formalities, Cody Technology Park, A4 Building, Room G016, Ively Road, Farnborough, Hampshire GU14 0LX (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: DIRECTION FINDING



(57) Abstract: Direction finding by radio comprises arranging an array of antennas (12), to receive signals from emitters, selecting individual antenna signals using a first multipole switch (SW1) and determining antenna signal strengths. Individual antenna signals are also selected by a second multipole switch (SW2), which routes a selected signal to a third multipole switch (SW3). The third switch (SW3) switches a phase shifter (P3) into and out of an antenna signal path. An adder (18) is employed to add an antenna signal in a first signal path extending via the first multipole switch (SW1) to a different antenna signal in a second signal path extending via the second and third switches (SW2, SW3). This determines combined signal strengths between pairs of antenna signals, one of which either has or has not been relatively phase shifted depending on the third switch position. Covariance matrix elements are determined from signal strengths enabling emitter bearings to be derived.

WO 2005/010550 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Declaration under Rule 4.17:

- of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report